

PRODUCT DATA

PRODUCT NAME: AK 102

PRODUCT DESCRIPTION : Water based Fire resistant, anti fungal, & anti microbial coating

RECOMMENDED USE: Applied on walls of hospitals, operation theatres and homes for clean environment and to provide fire resistance to class 1 surface spread of flame as per BS-476 part 7.

PHYSICAL DATA

COLOUR: Base white (Other shades provided on request)

FINISH Semi glossy / Matt

COVERAGE : 12 Sq mtr / ltr

DRYING CHARACTERISTICS :

Touch dry: 2Hours

Hard dry: 8 Hours

Full cure: 7 Days

(At 30 degree C and 65% Relative humidity)

SHELF LIFE: One year at room temperature

APPLICATION By Brush / By spray

THINNER: Clean Water

RECOMMENDED DFT: 30microns per coat

OVERCOATING INTERVAL MIN: 8 hours; MAX: 24 hours

If exceeds, the surface should be roughened by emery scuffing.

COMPATIBILITY Applied over all water based primer

RESISTANCE GUIDE

Fire : Meets the requirements of BS-476 part 6 & 7, IS-163 and ASTM 1360.

Acid : No effect (5 % HCl)

Alkali : No effect (5 % NaOH)

Water : No effect (40 degree C 7 days)

SURFACE PREPARATION

Clean the surface thoroughly of dust and water. Fill the gaps and cracks if any with cement putty before applying AK-102.

HEALTH & SAFETY

The product is water based and hence no special safety measures are required other than ordinary painting methods.

APPLICATION METHOD

Stir the paint thoroughly to attain homogeneity. Add clean water into the paint as required, depending on application method, and stir thoroughly for few minutes. Strain the paint through Nylon filter cloth of 400 mesh size and apply uniformly over the surface. The temperature of the substrate should be minimum 3°C above the dew point of the air, temperature and relative humidity measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure correct drying. All equipments used for above should be properly cleaned.

ADDITIONAL INFORMATION

Further information regarding industry standards, terms and abbreviations used in this data sheet contact us.

NOTES

1. Do not apply paint when temperature falls below 10°C or rises above 50°C and when Relative Humidity is above 85%, Do not apply during rain, fog, or mist.
2. Brushes and spray equipment should be cleaned with recommended thinner otherwise equipment is liable to damage.

DISCLAIMER

The information contained within this data sheet is based on information believed to be reliable at the time of its preparation. The company will not be liable for loss or damage howsoever caused including liability for negligence which may be suffered by the user of the data contained herein. It is the users' responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No

guarantee of results is implied since conditions of use are beyond our control.

Shukla Industries